Doc Code: AP.PRE.REQ

PTO/SB/33 (07-05)

Approved for use through xx/xx/200x. OMB 0651-00xx

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PRE-APPEAL BRIEF REQUEST FOR REVIEW		Docket Number (Optional)		
		NPI-51 (19673)		
I hereby certify that this correspondence is being deposited with the	Application N	Application Number Filed		
United States Postal Service with sufficient postage as first class mail in an envelope addressed to "Mail Stop AF, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450" [37 CFR 1.8(a)]	10/749,687		December 31, 2003	
on	First Named Inventor			
Signature	Francis Joseph Kronzer			
	Art Unit		Examiner	
Typed or printed name	1734		Sing P. Chan	
Applicant requests review of the final rejection in the above-identified application. No amendments are being filed with this request.				
This request is being filed with a notice of appeal.				
The review is requested for the reason(s) stated on the attached sheet(s). Note: No more than five (5) pages may be provided.				
I am the				
	J	MI	MUL	
applicant/inventor.			Signature	
assignee of record of the entire interest. See 37 CFR 3.71. Statement under 37 CFR 3.73(b) is enclosed.	Alan R. Marshall			
(Form PTO/SB/96)		Typed or printed name		
attorney or agent of record. Registration number 56,405	864-27	1-1592		
	phone number			
attorney or agent acting under 37 CFR 1.34.	Octobe	er 19, 2007		
Registration number if acting under 37 CFR 1.34			Date	
NOTE: Signatures of all the inventors or assignees of record of the entire interest or their representative(s) are required. Submit multiple forms if more than one signature is required, see below*.				
*Total of _1 forms are submitted.				

This collection of information is required by 35 U.S.C. 132. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11, 1.14 and 41.6. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop AF, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

PATENT

ATTORNEY DOCKET NO: NPI-51 (19673)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: Francis J. Kronzer) Examiner: Sing P. Chan
Serial No: 10/749,687) Art Unit: 1734
Filed: December 31, 2003) Account No: 04-1403
Confirmation No: 2173	Customer No: 22827
Title: Matched Heat Transfer Materials and Method of Use Thereof))

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

PRE-APPEAL BRIEF REQUEST FOR REVIEW

Dear Sir:

In conjunction with the filing of a Notice of Appeal, Applicants respectfully request review of the basis of rejections of pending claims 65-107, including independent claims 65, 100, and 104, in the present application. In the Final Office Action, independent claims 65 and 100 were rejected under 35 U.S.C. § 102(b) as being anticipated by U.S. Patent No. 6,017,636 to Tada, et al. Additionally, independent claim 104 was rejected under 35 U.S.C. § 103(a) as being obvious in view of Tada, et al.

<u>Tada, et al.</u> discloses five embodiments of a transfer system that employs a transfer layer formed from an emulsion-type urethane resin and preferably a ceramic micropowder. Only the second, fourth, and fifth embodiments disclose the use of two transfer sheets. Referring to Fig. 1, for instance, one embodiment of the transfer system of <u>Tada, et al.</u> employs a first transfer sheet A having the following layers:

Appl. No. 10/749,687 Pre-Appeal Brief Request dated Oct. 19, 2007 Reply to Office Action of June 21, 2007

- (1) Urethane emulsion resin layer 2 containing a ceramic micropowder; and
- (2) Release sheet 1.

The transfer system of Fig. 1 also employs a second transfer sheet B having the following layers:

- (1) Release sheet 3
- (2) Lower, heat-adhering resin layer 4;
- (3) Middle layer 5; and
- (4) Upper, heat-adhering resin layer 6 containing a pigment or micropowder.

According to these embodiments in <u>Tada</u>, et al., the image is disposed between the urethane emulsion layer 2 and the upper layer 6. The transfer methods of <u>Tada</u>, et <u>al.</u> result in the final image on the substrate coated with the urethane emulsion layer 2 to help protect the image.

A. <u>Tada, et al.</u> fails to teach or suggest an overlay transfer film that is "melt-flowable" at the transfer temperature

The urethane emulsion layer 2 of <u>Tada, et al.</u> has a specific softening point such that it can <u>prevent</u> the flow of a toner layer during heat-pressing. Col. 5, lines 13-16. Specifically, the urethane emulsion is said to preferably have a softening point of 140°C to 220°C, while transfer preferably occurs at a temperature of 120°C to 180°C. Cols. 4-5. Since these ranges overlap, the Office Action apparently concludes that the urethane emulsion layer 2 softens and flows at the transfer temperature. However, this conclusion contradicts the express teachings of <u>Tada, et al.</u> In fact, the entire purpose of <u>Tada, et al.</u> is directed to <u>preventing</u> melting and flowing of the toner layer through use of a non-flowable urethane emulsion layer 2. See, e.g., Col. 1, lines 26-31, lines 43-46; and Col. 5, lines 1-3, lines 13-16. Thus, <u>Tada, et al.</u> expressly requires that the

urethane emulsion layer 2 does <u>not</u> flow at the transfer temperature in order to prevent influence of the toner layer.

In stark contrast, independent claims 65, 100, and 104 of the present application require the use of an "overlay transfer film" that is "melt-flowable" at the transfer temperature. In this manner, the overlay transfer film may fuse or melt together with the "peelable transfer film" to form a matched "fused" laminate. Thus, Applicants respectfully submit that <u>Tada, et al.</u> fails to teach or suggest an overlay transfer film that is melt-flowable at the transfer temperature. As such, Applicants submit that independent claims 65, 100, and 104 are patentable over <u>Tada, et al.</u>

B. If the Office Action's interpretation of urethane emulsion layer 2 is upheld, contrary to the express teachings of <u>Tada</u>, <u>et al.</u>, then <u>Tada</u>, <u>et al.</u> fails to teach a melt-resistant layer that does not appreciably flow at the transfer temperature

If the urethane emulsion layer 2 of <u>Tada, et al.</u> is interpreted to melt and flow at the transfer temperature, contrary to the express teachings of <u>Tada, et al.</u>, then the other layers (i.e., the upper, middle, and lower layers) would also necessarily flow at the transfer layer. <u>Tada, et al.</u> teaches that these layers are positioned between the substrate and the image to attach the image to the substrate. According to <u>Tada, et al.</u>, the upper layer 6 becomes the background layer for the toner image layer after heat-transfer. The upper layer 6 is preferably formed from a urethane resin emulsion having a softening point of 140°C to 220°C. The lower layer 4 is preferably formed from a solvent-type urethane resin and polyester type resin, and softens and flows into the inner surface of the transfer object. The middle layer 5 functions to keep together the upper layer 6 and the lower layer 4, and is preferably formed from the same resin

composition as the lower layer 4. Col. 6. Undoubtedly, <u>Tada, et al.</u> requires that both the lower and middle layers soften and flow at the transfer layer.

In rejecting the pending independent claims, the Office Action states that the upper layer is formed of resin with a softening point of 80 °C to 200 °C. The Office Action concludes that the embodiments having a softening point above the transfer temperatures of 120 °C to 180 °C would not soften and flow. However, in making this conclusion the Office Action fails to take into account all of the teachings of <u>Tada, et al.</u> Tada, et al. states that the urethane resin emulsion described with reference to the urethane emulsion layer 2 can be used as the resin of the upper layer 6. In fact, in each of the disclosed embodiments having two transfer sheets (the second, fourth, and fifth embodiments), the upper layer 6 has the same resinous composition as its respective urethane emulsion layer 2. Thus, the urethane emulsion layer 2 and the upper layer 6 would have nearly identical softening and melt flow properties as each other.

As such, if <u>Tada</u>, et al. is interpreted as disclosing that the urethane emulsion layer 2 softens and flows at the transfer temperature (as attempted by the Office Action and contrary to the express teachings of <u>Tada</u>, et al.), then the upper layer 6 would also soften and flow at the transfer temperature. Under this interpretation, <u>Tada</u>, et al. fails to teach or suggest melt-resistant layer that is not appreciably melt-flowable at the transfer temperature.

C. Conclusion

In either interpretation of <u>Tada</u>, et al., Applicants respectfully submit that <u>Tada</u>, et <u>al.</u> simply fails to teach or even suggest the specific combination of a melt-flowable overlay transfer film (overlying the image) and a flow-resistant layer (positioned between

Appl. No. 10/749,687

Pre-Appeal Brief Request dated Oct. 19, 2007

Reply to Office Action of June 21, 2007

the image and the substrate), which is required by each independent claim of the

present invention. Thus, Applicants respectfully submit that Tada, et al. simply fails to

disclose or suggest all of the limitations of the method of independent claims 65, 100,

and 104. Applicants note that a claim is anticipated under 35 U.S. C. § 102 only if each

and every element as set forth in the claim is found, either expressly or inherently

described, in a single prior art reference. M.P.E.P. § 2131. Likewise, in order to

establish prima facie obviousness, all of the claimed limitations must be taught or

suggested in the prior art. See, e.g., MPEP § 2143.03.

D. Dependent Claims

None of the cited references teach or suggest that the melt flow index of a flow-

resistant layer is less than the melt flow index of an adhesive layer, such as required in

claim 83. Even further, the cited references completely fail to teach or suggest that the

melt flow index of a flow-resistant layer is less than the melt flow index of an adhesive

layer by a factor of at least 10, much less by a factor of at least 1000. As such,

Applicants respectfully submit that claims 83-85 are patentable over the cited

references.

Respectfully submitted,

DORITY & MANNING, P.A.

Date: October 19, 2007

Alan R. Marshall

Registration No.: 56,405

P.O. Box 1449

Greenville, SC 29602-1449

Phone: (864) 271-1592

Facsimile: (864) 233-7342

Page 5 of 5